

Installation guide

Packing bags -

PSA (M/L2/L1 - vehicle length 4,9 m)

VanEssa
mobilcamping



Mounting parts (included):

- One darkening plate per bag (pic. 2)

Note: In order to avoid moisture behind the bags, take them out from time to time and let them dry during the day.

1. Installation of the mounting kit:

- Slide the darkening plate between the lining and the window (pic. 2).

Note: Vehicle belts can still be used as usual.

The only requirement for attaching the PSA packing bag is that the rear of the van is panelled.



2. Packing bag installation

- Thread the back of the packing bag behind the aluminum strip on the blackout panel (pic. 3 + 4), then push the bags into the window until the bag is firmly on the fairing.
- The Velcro strap (red arrow, pic. 2) has two functions. It is used to remove the darkening plate and to prevent the packing bag, which also has Velcro at the bottom, from falling out.

Note: The handy features enable direct and fast access to your glasses (pic- 5a), keys (pic. 5b), mobile (pic 5c), etc - close at hand next to your roost.



If you have any further questions please contact us:

+49 (0) 8063 / 20 760 - 0 or info@vanessa-mobilcamping.de

VanEssa mobilcamping | Lauser Strasse 27 | 83620 Grosshöhenrain | Deutschland
Tel. +49 (0) 8063/20 760-0 | info@vanessa-mobilcamping.de