

Installation guide

Packing bags Mercedes Marco Polo (with kitchen installation)

VanEssa
mobilcamping



1. Preparation

- Prior to the installation, the back plate of the bag needs to be in the right position. While delivery, the back plate may slip under the top/bottom plate of the bag.
- If the case may be, push onto the top/bottom plate, for the plate slipping back in a lateral position (pic. 1).
- Take notice of the correct side: the VanEssa logo shows towards the boot (pic. 2).



Note: In order to avoid moisture behind the bags, take them out from time to time and let them dry during the day.

2. Variant with sun blind from above (pic. 3)

We recommend to be two persons for installation: One person holding the sun blind a little off the window (pic. 4+5), the other person installing the bag as described below.



3. Packing bag installation

- Fold the lateral flap and place the bag in the window with the bag flush with the inner side of the window. Thread the back plate of the bag behind the rubber lip, first of all at the bottom, then at the top.


Tip: Threading the bag behind the bottom rubber lip gets easier, when you dismantle the hook of the sun blind before (red circle, pic. 4).

- Push the bag in the direction of the boot. The slot fits around the window engine, in case you have one (pic. 6).
- Flap the flap into the window until the plate also engages behind the rubber lip (pic. 7).
- As an additional tilt prevention, you can fix the cord on the hook under the handhold. Therefore open the zipper of the upper compartment and push the bag a little upwards (pic. 8).
- Additionally you may put the aluminium support bar between the vehicle lining and the window (pic. 9).



4. Outer applications

- You can deposit important everyday objects like cell phones (pic. 10a), keys (pic. 10b) or sunglasses (pic. 10c) in/at the additional applications on the outside of the packing bags.



If you have any further questions please contact us: +49 (0) 8063 / 20 760 - 0